# TINY SIZE / WEATHERPROOF CAMERA

## CTT-1601

## Features

- 1/3" Sony color CCD sensor
- Razor Sharp High Resolution : 480 (H) TV Line
- 0.1 Lux
- 12 volts DC power source, 120mA power consumption
- 3.6mm fixed lens installed
- Sun-Visor, Weatherproof
- Auto Trace White Balance(ATW)
- Back Light Compensation(BLC)
- Electronic Shutter Control (ESC)
- Auto Gain Control (AGC)
- Mount bracket included

## Specifications

| | |
|---|---|
| MODEL | CTT-1601 |
| Image Sensor | 1/3" Super HAD Color CCD |
| Effective Pixels | NTSC: 768 (H) x 494 (V), PAL: 752 (H) x 582 (V) |
| Sensing Area | 3.85(H) x 2.74(V) mm |
| Scanning System | 525 Lines, 60 Field/Sec (NTSC)<br>625 Lines, 50 Field/Sec (PAL) |
| Horizontal Resolution | 480 TV Lines |
| Minimum Illumination | 0.1 Lux / F2.0 |
| Shutter Speed | 1/60 ~ 1/100,000 Sec (NTSC)<br>1/50 ~ 1/100,000 Sec (PAL) |
| S/N Ratio | More than 48dB |
| Gamma Characteristic | 0.45 |
| Lens | 3.6mm fixed board lens |
| Video Output | 1.0Vp-p, 75 Ω |
| Power | 12V DC / ±10% / 120mA |
| Operational Temperature | -10°C ~ 50°C(14°F~122°F) RH 95% Max |
| Dimensions | 21.5(W) x 22.5(H) x 77(L)mm |
| Weight | 0.2lbs |
| White Balance | Auto tracking white balance |
| Body | Aluminum |

## Connections



SVA Group USA Inc.
1316 John Reed Court, City of Industry, CA 91745
Tel: 626-363-9500 | Fax: 626-363-9508
1-888-8-ASK-SVA
http://www.sva-usa.com